# C-TECH RUBBER PIPE PRODUCTS

# MASTIC PRIMER MPO1

#### **APPLICATION**

- 1. Stir primer prior to use.
- 2. Brush apply onto clean dry surface.
- 3. Leave to air dry a minimum of 5 minutes before applying tape.

#### **CLEAN UP**

- Use mineral turpentine.
- Wipe up spills immediately with dry cloth.

#### STORAGE

12 months shelf life if stored below 28°C and in shade.

**FIRST AID** 

If poisoning occurs, contact doctor or Poisons Information Centre. If swallowed, do not induce vomiting. Give a glass of water. Poisons Information Centre Ph. 131126 (Australia).

# **Safety Directions**

#### **HIGHLY FLAMMABLE**

- Avoid contact with skin and eyes and avoid breathing vapours.
- · Avoid contact with food.
- Do not swallow.
- Wear protective clothing, gloves and glasses while in use. If clothing becomes contaminated remove and wash before re-use.
- Keep containers sealed when not in use. Store and use in a well ventilated area.
- Do not use near spark producing tools or clothing.
- Take precautionary measures against static discharges.
- Keep away from heat, flames and other source of ignition.

"Mastic Primer MPO1" is used for the priming of a surface before the laying of mastic tape.



# C-TECH RUBBER P/L

**C-Tech**Sealant Products

ABN - 85 - 003 704 612 17 Devon Road Ingleburn NSW 2565 Australia In Australia:

PHONE: (02) 9829 3022 FAX: (02) 9829 4085

International Calls:

PHONE: 61-2-9829 3022 FAX: 61-2-9829 4085

# C-TECH RUBBER MATERIAL SAFETY DATA SHEET

# **BUTYL MASTIC PRIMER**

#### 1. Identification of the substance / preparation and the company Butyl Mastic Primer

C-Tech Rubber Pty Ltd

17 Devon Rd, Ingleburn, NSW 2576

Phone: (02) 9829 3022, Fax: (02) 9829 4085

#### 2. Composition / Information on Ingredients

Chemical Name: Butyl Rubber Solution

Contains: Toluene, White Spirits, Butyl Rubber (IIR), Polybutene, Carbon Black,

Phenolic Resin.

#### 3. Hazard Information

Skin: Avoid contact with skin. Wear protective clothing and gloves.

Eye Contact: Avoid eye contact. Wear protective glasses or goggles.

Ingestion: Do not swallow.

Respiratory: Avoid breathing vapours.

#### 4. First Aid Measures

Skin: If clothing becomes contaminated, remove and wash.

Eye Contact: Rinse eyes thoroughly with water for at least 15 minutes. Consult a doctor.

Ingestion: If swallowed, do not induce vomiting. Give a glass of water. If poisoning occurs, contact doctor or Poisons Information Centre. **Poisons Information Centre - Ph. 131 126** (Australia)

Respiratory: Remove to fresh air. Consult a doctor if further symptoms persist.

#### 5. Fire Fighting Measures

Extinguishing Media: CO<sub>2</sub>, Dry Chemical, Foam or Water Spray. Avoid straight water streams, though water spray may be used to cool fire.

Fumes: Respirators are necessary in case of fire fighting.

#### 6. Accidental Release Measures

Collect by mechanical means. Mineral Turpentine may aid in cleanup.

# 7. Handling and Storage

Store and use in a well ventilated area. Keep away from heat, flame and other sources of ignition. Avoid static discharges and do not use near spark producing tools or clothing. Keep containers sealed when not in use.

# 8. Exposure Controls / Personal

Eye Protection: Wear protective eye-wear when splashing is possible.

Hand Protection: Wear gloves.

Respiratory Protection: Approved organic vapour chemical cartridge should be worn if working in areas with inadequate ventilation.

# 9. Physical and Chemical Properties

Form: Viscous liquid.

Colour: Black.

Solubility in Water: Insoluble.

Soluble in: Aromatic and aliphatic hydrocarbons.

Flash Point: Not Known.

# 10. Stability and Reactivity

Auto ignition temperature: 480°C.

In case of fire, be aware of noxious fumes being given off.

#### 11. Toxicological Information

No data available.

# 12. Ecological Information

No data information.

# 13. Disposal Information

Dispose of in a manner consistent with federal, state and local regulations.

# 14. Transport Information

UN NO 1993

FLAMMABLE LIQUID

N.O.S PG 11

HAZCHEM 3(Y)

# 15. Regulatory Information

Product must be labelled with above transport information. Classified as a class 3 flammable liquid.

The purpose of this Data Sheet is to describe the product in terms of its safety requirements. The information here is based on current knowledge and experience. Supplier is not responsible for injury or liability following the misuse of this product.